



- NOTES:-
1. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL OTHER RELEVANT DRAWINGS, ANY DISCREPANCIES, ERRORS OR OMISSIONS ARE TO BE BROUGHT TO THE ATTENTION OF CAPITA.
 2. ALL DIMENSIONS TO BE CHECKED BEFORE COMMENCEMENT OF WORKS ON SITE.
 3. ALL DIMENSIONS IN METERS UNLESS OTHERWISE STATED.
 4. ALL SETTING OUT TO BE AGREED WITH THE PROJECT MANAGER.
 5. ALL PEDESTRIAN CROSSING POINTS SHALL BE AGREED WITH THE PROJECT MANAGER.
 6. COLOUR OF TACTILE PAVING TO BE 'RED' FOR CONTROLLED CROSSING POINTS.
 7. COLOUR OF TACTILE PAVING TO BE 'BUFF' FOR UNCONTROLLED CROSSING POINTS.

- KEY:
- PROPOSED FOOTWAY CONSTRUCTION FC 1
100mm DEPTH OF GRANULAR TYPE 1 SUB-BASE. 50mm THICK SEMI DRY MORTAR MIX 3:1 SAND / CEMENT. 450 X 450 X 50mm BLISTER TACTILE PAVING. REFER TO STANDARD DETAIL DRAWING NO. H076063-01-STD-1100-001&0002.(20m²)
 - PROPOSED FOOTWAY CONSTRUCTION FC 2
100mm DEPTH OF GRANULAR TYPE 1 SUB-BASE. 45mm THICKNESS OF AC 20 DENSE BIN 100 / 150 REC TO EN13108-1:2006 AS BINDER COURSE 20mm DEPTH OF AC 6 MED SURF 160/220 TO BSEN13108-1:2006 AS SURFACE COURSE. REFER TO STANDARD DETAIL DRAWING NO. H076063-01-STD-1100-0003.(40m²)
 - PROPOSED FOOTWAY CONSTRUCTION FC 2
EXISTING TARMAC FOOTWAY TO BE EXCAVATED AND CARTED TO TIP OFF SITE. EXCAVATION DEPTH TO BE 20mm OF SURFACE. 20mm DEPTH OF AC 6 MED SURF 160/220 TO BS EN 13108-1:2006 AS SURFACE / REGULATING COURSE AS OVERLAY. REFER TO STANDARD DETAIL DRAWING NO. H076063-01-STD-1100-0003.(152m²)
 - PIGMENTED UV STABILISED COLD APPLIED RESIN BINDER WITH CRUSHED GRANITE OR SYNTHITE GREEN AGGREGATE 1:1 MIX 1.5mm AND 3mm NOMINAL SIZE. OR SIMILAR APPROVED.(8.5m²)
 - 125 X 255mm PCC HALF BATTERED KERB WITH 150mm THICK GRADE ST4 CONCRETE BED AND HAUNCH. 100mm KERBFACE UNLESS OTHERWISE STATED. REFER TO STANDARD DETAIL DRAWING NO. H-076063-01-STD-1100-0004.(5m)
 - 50 x 150mm PCC RECTANGULAR SQUARE TOP EDGING WITH 100mm THICK GRADE ST4 CONCRETE BED AND DOUBLE HAUNCH LAID FLUSH REFER TO STANDARD DETAIL DRAWING NO. H-076063-01-STD-1100-0004.(73m)
 - E1 CYCLIST CROSSING POINT COMPRISING 2 NO. TAPER KERBS AND REQUISITE NUMBER OF 125 x 150mm BULLNOSED KERB 'K4' LAID FLUSH REFER TO STANDARD DETAIL DRAWING NO. H-076063-01-STD-1100-0001&0002.(39m)
 - CX3 PEDESTRIAN CROSSING POINT COMPRISING 2 NO. TAPER KERBS AND REQUISITE NUMBER OF 125 x 150mm BULLNOSED KERB 'K3' SET AT 6mm FINISHED FACE. REFER TO STANDARD DETAIL DRAWING NO. H-076063-01-STD-1100-0001&0002.(14m)
 - PX3 EXISTING BOLLARDS TO REMAIN. (4 No.)
 - PROPOSED PEDESTRIAN VISIFLEX GUARDRAILS. REFER TO STANDARD DETAIL DRAWING NO. H-076063-01-STD-400-0001.(4m)
 - EXISTING MANHOLE CHAMBER TO REMAIN.
 - EXISTING DOUBLE BT MANHOLE CHAMBER TO REMAIN
 - RS 'DUCKFOOT' RETENTION SOCKET TO BE INSTALLED BY CONTRACTOR. TRAFFIC SIGNAL POLE AND HEAD TO BE INSTALLED BY CLIENT. REFER TO STANDARD DETAIL DRAWING NO. H-076063-01-STD-500-0002.(2 No.)

C01	CONSTRUCTION	DR	APN	MAE	MAR 16
P01	ISSUE FOR PRICING	SCC	APN	MAE	OCT 15
REV	DESCRIPTION	DRAWN	CHK	APP	DATE

CAPITA
 CASTLEWAY HOUSE
 17 PRESTON NEW ROAD
 BLACKBURN
 BB2 1AU
 TEL: (01254) 273000
 FAX: (01254) 273559
 www.capita.co.uk

status: CONSTRUCTION

client: BLACKBURN WITH DARWEN B.C.
 TOWN HALL
 BLACKBURN BB1 7DY



project title: WEAVERS WHEEL Ph2 2016_17

drawing title: WORKS PACKAGE 5
 PROPOSED FOOTWAY CONSTRUCTION AND KERBING DETAILS-WITTON PARK ENTRANCE

scale @ A1	designed by	drawn by	checked by	approved by	date drawn
1:100	SCC	SCC	APN	MAE	OCT 15

project no: CS076063-01
 drawing no: H-076063-01-1105-0002
 revision: C01

Do Not Scale From This Drawing

THIS DRAWING IS COPYRIGHT TO CAPITA ENGINEERING LIMITED. IT SHALL NOT BE USED WITHOUT PERMISSION FOR ANY PURPOSE. REPRODUCTION IS ONLY PERMITTED BY PRIOR ARRANGEMENT.